



Specifications Ledvance LED  
Downlight Performance DN195 Zigbee  
White 21W 2520lm - 840 Cool White |  
220mm - Cutout 195mm

[View Product](#)

General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 243657                                  |
| EAN                      | 4058075459397                           |
| Brand                    | Ledvance                                |
| Manufacturer Name        | DL UGR19 DN195 PFM 21W/840 ZBVR WT LEDV |
| Any Lamp all-in warranty | 3 Years                                 |
| Average Lifetime (h)     | 70000                                   |

Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tilttable                   | No                |
| Technology                  | LED Integrated    |
| Wireless connection         | Zigbee            |
| Lighting Control            | Zigbee            |
| Wattage                     | 21                |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Dimmable          |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                          |                                |
|--------------------------|--------------------------------|
| Light colour options     | Single Color                   |
| Including bulb           | Yes                            |
| Beam Angle (degree)      | 65                             |
| Luminous Flux (Lumen)    | 2520                           |
| Luminous Efficacy (lm/W) | 120                            |
| Power factor             | >0.90                          |
| Installation Depth (mm)  | 120                            |
| Unified Glare Rating     | < 19 - for offices and schools |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 195               |
| IP-rating              | IP54              |
| Impact Protection (IK) | IK03 - 0.35 joule |
| Operating Temperature  | -20 to +45        |
| Housing                | Aluminium         |
| Colour of the Fixture  | White             |
| Colour of material     | White             |
| Series                 | DN195             |

## Dimensions

Height (mm)

**Why Any-lamp?**

65

Diameter (mm)

220



Order from the **largest lighting specialist** in Europe



**Customised** quotation

## Sensor Information



Up to **7 years warranty**



**Easy** return process

Type of sensor

No Sensor

