



Specifications Ledvance LED Panel  
Compact 35W 3850lm - 830-840 CCT |  
60x60cm - UGR <19 - Dali Dimmable

[View Product](#)

## General Information

|                          |                                                         |
|--------------------------|---------------------------------------------------------|
| SKU                      | 250540                                                  |
| EAN                      | 4099854206603                                           |
| Brand                    | Ledvance                                                |
| Manufacturer Name        | PANEL COMPACT 600 UGR<19 DALI 2CCT 35W 830 840 U19 DALI |
| Any Lamp all-in warranty | 5 Years                                                 |
| Average Lifetime (h)     | 50000                                                   |
| Series                   | Compact                                                 |

## Technical Information

|                             |                                  |
|-----------------------------|----------------------------------|
| Technology                  | LED Integrated                   |
| Replaces (Watt)             | 4x18                             |
| Wattage                     | 35                               |
| Voltage (V)                 | 220-240                          |
| Dimmable                    | Dimmable with Dali               |
| Colour Code                 | 830 Warm White, 840 Cool White   |
| Colour temperature (Kelvin) | 3000 Warm White, 4000 Cool White |
| Colour Rendering (Ra)       | 80-89                            |
| Colour of Light             | White                            |
| Light colour options        | CCT                              |
| Luminous Flux (Lumen)       | 3850                             |

|                          |                    |
|--------------------------|--------------------|
| Luminous Efficacy (lm/W) | 110                |
| IP-rating                | IP40               |
| Impact Protection (IK)   | IK02 - 0.20 joule  |
| Fixture Connection       | Screwless terminal |
| Power factor             | >0.90              |
| Product Type Category    | LED Panel          |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Operating Temperature | -10 to +50                     |
| Emergency Lighting    | Optional: Emergency Light      |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |         |
|----------------|---------|
| LED panel size | 60x60cm |
| Length (mm)    | 595     |
| Width (mm)     | 595     |
| Height (mm)    | 32      |

## Sensor Information

## Why Any-lamp?

Type of sensor

No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process

